

la  
mic  
1600SE

MAGENTA-VISION



## AUTO HOT/COLD LAMINATOR

### Multi-Function

### SINGLE HOT/COLD LAMINATOR

High-performance laminator suitable for industrial applications. It allows laminating, mounting and encapsulating prints, applying application tape and double-sided adhesive; compatible with all kinds of cold laminating film in the market.




Magenta Vision Polska Sp. z o.o.  
Okulickiego 26, 05-500 Piaseczno, Poland  
[support@magenta-vision.com](mailto:support@magenta-vision.com)



• Rear Control Panel

• Optional Cutting Device



◎ Professional sturdy and robust laminator designed to guarantee every day high quality results with great speed.


◎ 64" ALUMINUM SHAFTS (total 5 shafts) for easy loading and unloading of the rolls.

◎ It can support big and heavy rolls with diameter up to 200mm thanks to the increased distance between rollers and support shafts.


◎ Heated upper roller with preset electronic temperature regulation – standard on 1600 model (Room~120°C)

◎ Ideal for mounting images on panels even of large dimensions, for encapsulations or for applying at the same time a plastic lm and a double-sided adhesive for mounting


◎ Intuitive set up parameters thanks to the user-friendly control panel.



Laminating with cutting



Liner film laminating



Liner Guide Rail Way  
Limits The Roller Lifting  
Vertically;



Automatic Clamp device;  
Auto-stop Feeding  
Monitored



Power Failure Protection  
Device;  
Cutting Position Allows  
Full Directions Adjustment.



Meter Counting  
Function  
666m

Model	1600SE
Max laminating width	1620mm
Max laminating thickness	35mm
Max Speed	15m/min
Max temp	Room~120°C
Heating	Infrared
Preheating time	10~15min
Roller upgrade	Air cylinder
Power input	0.8~2.5kw/h
Volt	110/220V
Roller material	silicon
N.W	250kg