



Magenta Vision Polska Sp. z o.o.
Okulickiego 26, 05-500 Piaseczno, Poland
support@magenta-vision.com

TECHNICAL PARAMETER

Air Pump Power	7.5KW	7.5KW	9KW
Fixed Power	9.5KW	9.5KW	11KW
Effective Cutting Area	2500*1300mm	2500*1600mm	3000*2000mm
Overall Size	3900*2285*1350mm	3900*2585*1350mm	4400*2985*1350mm
Cutting Speed	300-1800mm/s (according to different materials)		
Cutting Thickness	≤ 50MM (according to different materials)		
Working Environment	Temperature: 0° -35° Humidity: 35%-80%		
Transmission System	High-end servo motor drive, imported linear guides, bearings		
Working Voltage/Power	AC 380V/220V±10%50HZ		
File System	Compatible with HPGL/PLT/DXF etc. Repeat accuracy ≤ 0.01mm Software resolution 0.025		

Working Characteristics	Can be connected to any CAD software, computer-aided design and cutting can be carried out at the same time
Buffer Capacity	One-time quick transfer sheet-fed cutting
Transmission Port	Standard network port
Fixed Method	Vacuum adsorption
Operation Interface	Touch Screen
Feeding Method	Imported crawler automatic feeding method (can be cut in unlimited length)
Standard Tools	High-speed oscillating tool, universal cutting tool, kiss-cut tool, CCD automatic positioning system, cursor
Optional Tools	Pen, V-CUT, creasing wheel, milling tool set, 50MM foam cut tool
Cutting Material	All kinds of corrugated cardboard, Yellow cardboard, Red cardboard, PVC board, Honeycomb board, PVC foam board, Acrylic, KT board, Aluminum-plastic board, Fiber midsole and rubber board, Thick foam, Car sticker, adhesive, Reflective film, Photo paper, Photo PVC, etc.